

Product and Technical News in Oct. 2018

T1

XONE: V1.0.1.0

TONE: V1.11

● Update

1. The update for XTOOL(V1.0.0.29)

1) VENUS X3 and VENUS X7 can be updated via TONE. Connect X3 or X7 to TONE via RS232 for update.

2. The update for XONE(V1.0.1.0)

1) Two Switching Mode for T-Bar are added, including Swap Mode and One way Mode.

2) For H.264 IP streaming preview function:

A. The H.264 output core software version can be checked on T-ONE. The setting of IP, MAC, resolution and frame rate on H.264 output module is available.

B. Add rtmp address and audio output for H.264 output module.

C. The signal is free to select for H.264 IP streaming preview.

3) Add the pre-setting function for Tab button. Press Fn+Tab buttons to switch the options on main menu bar.

4) To control VENUS X7, the Banks on PST and PGM would be sync automatically.

5) Add the setting for 4K@60 input module.

6) The "PREVIEW" character can be shown or hidden by pressing the Show or Hide buttons.

7) The output resolution 1920*1080@23.98, 1920x1080@24, 1920*1080@25, 1920*1080@29.97 is available.

8) Add Source Merge function.

9) The function of the buttons on FUNCTION area is available.

10) The function of LOCK, BLACK, MATCH PGM, FREEZE PST, FREEZE PGM is available.

Address: S601 Weiye Building Torch Hi-Tech Industrial Development Zone Xiamen, Fujian P.R.C

Tel: 4008 592 315

Fax: +86 592 5788216

Email: support@rgblink.com <http://www.rgblink.com>

1 / 4

11) Add the T-Bar correction function.

- **Optimization**

1. The optimization for the followings:

- 1) The Link Mode of X3.
- 2) To control X3 and X7, the switching effect of T-Bar.
- 3) The 4K@30 input setting.
- 4) The LOGO capture function.
- 5) The input property setting for D-HDMI and D-SDI input modules.
- 6) Turn on Select Take switch, the bank would be switched to next one for PST when TAKE switching is finished.
- 7) The Copy Bank and Paste Bank function.
- 8) The layer operator for X3 and X7.
- 9) The Display System:
 - A. The Container function is removed.
 - B. The size of Container bar can be changed.
 - C. The function of Delete all containers is added.

- **Problem Solved**

1. The XONE system would crash during the operation.

2. When the setting for system time is done and reboot, the data cannot be saved.

Instructions:

1. For the update and optimization above, the software version of X3 must be V2.33 or higher, and the software of X7 must be V2.53 or higher.
2. The software version of H.264 for X7 must be V2.9 or higher.
3. The H.264 output module must be plugged into the 7th or 8th output slots on X7.

- **Download link for latest software**

(EN) https://rgblink.com/en/products_detail.aspx?id=741

Address: S601 Weiye Building Torch Hi-Tech Industrial Development Zone Xiamen, Fujian P.R.C

Tel: 4008 592 315

Fax: +86 592 5788216

Email: support@rgblink.com <http://www.rgblink.com>

2 / 4

(CN) https://www.rgblink.cn/products_detail.aspx?id=740

Contact sales or customer support personnel of RGBlink to get the latest software.

M2

Version: V2.03

- **Optimization**

- 1. Solved PVW system lagging issue.**
- 2. The limitation of layer A crop setting would be effective when 3-layer display is available.**

- **Download link for latest software**

(EN) <https://rgblink.com/product-detail?id=713>

(CN) https://www.rgblink.cn/products_detail.aspx?id=712

Contact sales or customer support personnel of RGBlink to get the latest software.

RMS 8424-1A DMT

Version: V2.20

- **Optimization**

- 1. The DMT custom boot screen is uploaded.**
- 2. The automatic detection for DVI, USB and VGA inputs is added.**

- **Download link for latest software**

Contact sales or customer support personnel of RGBlink to get the latest software.

V2

Version: V1.29

Address: S601 Weiye Building Torch Hi-Tech Industrial Development Zone Xiamen, Fujian P.R.C

Tel: 4008 592 315

Fax: +86 592 5788216

Email: support@rgblink.com <http://www.rgblink.com>

- **Optimization**

- 1. Solved the EDID recognition problem for HDMI and DVI input modules.**

- 2. The name of optional input channel is fixed. For example, the name of DVI optional input is changed to “M-DVI”.**

- **Download link for latest software**

- (EN) https://rgblink.com/en/products_detail.aspx?id=758

- (CN) https://www.rgblink.cn/products_detail.aspx?id=762

Contact sales or customer support personnel of RGBlink to get the latest software.