

AI mini Wireless Microphone



Key Features

- Equipped with a dedicated noise cancellation button, supports one-touch noise cancellation
- Support reverb stereo sound effects
- Support mute mode
- The transmitter supports the earphone monitoring function
- Support external playback of sound when connected to a mobile phone

Specification

Performance	Wireless Transmission	2.4GHz		
	Frequency Response	20Hz~20KHz		
	Directionality	360-Degree Omnidirectional		
	Working Range	≤40 meter (Under unobstructed conditions, actual performance is affected by the environment)		
	Sensitivity	2m		
	Signal-to-Noise Ratio	75dB		
	Latency	20ms		
	Mic	Professional Capacitor Microphone with Noise Reduction		
	Noise Reduction Method	Dual Noise Reduction		
	Electric Current	Operating Current	<14ma	
		Standby Current	<7ua	
	Battery Capacity	Transmitter	80mAh	
		1-to-2 Charging Case	650mAh	
	Battery Capacity	Transmitter	8H	
	Battery Life	120 Minute		
Pairing Method	Automatically searches and pairs upon powering on			
Charging Port	TX	Type-C port		
	RX	Type-C or iPhone port		
	Charging Case	Type-C port		
Charging Input Voltage	DC 5V			
Environment	Operating Temperature	10°C~45°C		
Physical	Weight	TX	9.0g	
		RX	3.0g	
		1-to-2 Charging Case	77.0g	
	Dimensions	TX	28.4 × 21.8 × 29.4mm	
		RX	40.0 × 9.5 × 18.7mm	
1-to-2 Charging Case		84.0 × 40.0 × 51.0mm		
Packing List	Microphone transmitter, Lightning receiver, Charging cable, Charging box, User manual			

Order Codes

Product Code	Item
964-0011-01-0	AI mini Wireless Microphone

Tel: +86-592-5771197 | Fax: +86-592-5788216 | E-mail: sales@rgblink.com

Headquarter: Room 601A, No. 37-3 Banshang community, Building 3, Xinke Plaza, Torch Hi-Tech Industrial Development Zone, Xiamen, China

Specifications are correct at time of printing and subject to change or alteration without notice.



www.rgblink.com